



Multi-Conductor - Audio/Spker Cable			
General Description :	16 AWG, 2 Conductor, CMR/CL3R Sound Audio Cable, Stranded Oxygen Free High Conductivity Bare Copper Conductors		
Physical Characteristics :	Conductors	AWG	Stranding
	2	16	65 x 0.0063"
	Dielectric Material		Nom. Dielectric Conductor Dia.
	PVC		0.083" ± 0.004"
	Jacket Material		Nom. Jacket Thickness
	PVC		0.0216"
	Outer Shield Material		Nom. Overall Diameter
Unshielded		0.209" ± 0.006"	
Mechanical and Electrical Characteristics :	Temperature Rating	Operating Voltage	Nominal Weight
	(-) 20°C to (+) 75°C	300 V	14.5 lbs
	Nom. DCR per Conductor @ 20°C		4.18 Ω / 1,000ft.
Cable Marking :	Geintech 16AWG*2C 75C E335585-T CL3R (UL) OR E329281-T CMR (UL) C(UL) MM/DD/YYYY RoHS COMPLIANT ***FT		

Part #	Color	Put-up	
A162BL-500	Blue	500'	Reelex Box
A162WH-500	White	500'	Reelex Box

Insulation Colors	
1	Black
2	Red

Approval :	
National Electrical Code : Article 800	UL Standard 444 Type CMR (UL)
National Electrical Code : Article 725	UL Standard 13 Type CL3R



Geintech Technologies, Inc. 14403 Ramona Ave, Unit B, Chino, CA 91710 Toll Free: 855.606.7722 www.GEINTECH.com