



Multi-Conductor - Audio/Spker Cable				
<b>General Description :</b>	16 AWG, 4 Conductor, CMR/CL3R Sound Audio Cable, Stranded Oxygen Free High Conductivity Bare Copper Conductors			
<b>Physical Characteristics :</b>	Conductors	AWG	Stranding	
	4	16	65 x 0.0063"	
	Dielectric Material		Nom. Dielectric Conductor Dia.	Nom. Dielectric Thickness
	PVC		0.083" ± 0.004"	0.0122"
	Jacket Material		Nom. Jacket Thickness	Rip Cord
	PVC		0.0216"	Nylon
	Outer Shield Material		Nom. Overall Diameter	Minimum Spot
<b>Mechanical and Electrical Characteristics :</b>	Temperature Rating		Operating Voltage	
	(-) 20°C to (+) 75°C		300 V	
	Nom. DCR per Conductor @ 20°C		4.18 Ω / 1,000ft.	
<b>Cable Marking :</b>	Geintech 16AWG*4C 75C E335585-T CL3R (UL) OR E329281-T CMR (UL) C(UL) MM/DD/YYYY RoHS COMPLIANT ***FT			

Part #	Color	Put-up	
A164BL-500	Blue	500'	Reelex Box
A164WH-500	White	500'	Reelex Box

Insulation Colors	
1	Red
2	Black
3	White
4	Green

Approval :	
National Electrical Code : Article 800	UL Standard 444 Type CMR (UL)
National Electrical Code : Article 725	UL Standard 13 Type CL3R



Geintech Technologies, Inc. 14403 Ramona Ave, Unit B, Chino, CA 91710 Toll Free: 855.606.7722 www.GEINTECH.com