



Multi-Conductor - Audio/Speaker Cable				
General Description :	14 AWG, 2 Conductor, CMR/CL3R Sound Audio Cable, Stranded Oxygen Free High Conductivity Bare Copper Conductors			
Physical Characteristics :	Conductors	AWG	Stranding	
	2	14	105 x 0.0063"	
	Dielectric Material		Nom. Dielectric Conductor Dia.	Nom. Dielectric Thickness
	PVC		0.104" ± 0.004"	0.016"
	Jacket Material		Nom. Jacket Thickness	Rip Cord
	PVC		0.0228"	Nylon
	Outer Shield Material		Nom. Overall Diameter	Minimum Spot
Unshielded		0.256" ± 0.006"	0.016"	
Mechanical and Electrical Characteristics :	Temperature Rating		Operating Voltage	
	(-) 4°F to (+) 167°F		300 V	
	Nom. DCR per Conductor @ 20°C		2.62 Ω / 1,000ft.	
Cable Marking :	Geintech 14AWG*2C 75C E335585-T CL3R (UL) OR E329281-T CMR (UL) C(UL) MM/DD/YYYY RoHS COMPLIANT ***FT			

Part #	Color	Put-up	
A142BL-500	Blue	500'	Reelex Box
A142WH-500	White	500'	Reelex Box

Insulation Colors	
1	Black
2	Red

Approval :	
National Electrical Code : Article 800	UL Standard 444 Type CMR (UL)
National Electrical Code : Article 725	UL Standard 13 Type CL3R

Geintech Technologies, Inc. 14403 Ramona Ave, Unit B, Chino, CA 91710 Toll Free: 855.606.7722 www.GEINTECH.com					